

Green Radiator Corrosion Protector (RCPG)

Nulon Radiator Corrosion Protector - protects your cooling system from rust and corrosion for 3 years or 100,000km no matter the age or metal type. NOTE: For vehicles that require a Type A OEM replacement coolant use Nulon Long Life Coolants, available in both Concentrate and Pre-Mixed variants.

Benefits

- Contains advanced long-life inhibitor technology for maximum corrosion protection of all cooling system metals for 3 years or 100,000km
- · Protects aluminium, steel, cast iron, solder, copper and brass
- Safe for all hoses, gaskets and seals
- Exceeds Australian AS 2108-2004 Type B standard



Directions for use

DIRECTIONS FOR SERVICE REFILL: Refer to the owner's manual for cooling system capacity. If the cooling system is dirty we recommended using Nulon Radiator Flush before using this product.

- 1. If the system is clean, ensure the engine is switched off, turn the heater on and drain the old coolant (when cool) by removing the drain plug or bottom radiator hose.
- 2. Replace drain plug or bottom radiator hose.
- 3. Add NULON RADIATOR CORROSION PROTECTOR to the radiator first then topup with clean, soft or demineralised water. (Makes up to 20 Litres)
- 4. Check the coolant level is correct when system is cool.

Safety Direction

SAFETY: Harmful if swallowed. May cause respiratory irritation. Use only outdoors or in a well-ventilated area. Store locked up.

FIRST AID: IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Rinse mouth. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. For advice, contact a Poisons Information Centre (e.g. phone Australia 13 11 26; New Zealand 0800 764 766) or a doctor (at once).

ENVIRONMENT: Do not pollute drains, soil or water with used products. After use, dispose of container in a responsible manner. Disposal of container should comply with local council regulations.

Meets or exceeds the following oil industry specifications	
AS Claims	AS 2108-2004 Type B
ASTM	ASTM D3306, ASTM D4985
Society of Automotive Engineers	SAE J1034, SAE J1941

Pack Sizes



Part No: RCPG-500 500 ml - 6 Per Carton Barcode: 9311090 004825

Part No: RCPG-1 1 Litre - 6 Per Carton Barcode: 9311090 004696